

T 12 S T 12 L

MAXIMUM PAYLOAD FOR SMALL TRUCKS

36-1/4" pickup bar height, sliding jib, single jib cylinder equipped with single counterbalance valve and dual tipping cylinders equipped with dual counterbalance valve, jib interlock, 6-1/4" subframe height, dual lever in cab electric controls, direct mount axial piston pump and aluminum valve body and junction box cover.

T 12 S - HOOKLIFT HOIST (short)

FEATURES:

- 12,000 lb. capacity
- 10' - 12' container length range
- 52 degree dump angle
- Chassis requirements: 2 axle, 18,000 lb. recommended GVWR with 84" CA.



Model	Capacity in LBS	Container Length (ft.)	Dump Angle	Recommended Dimension (Inches)		Recommended GVW Rating (lbs)
				CA (4X2)	CT (6X4)	
T 12 S	12,000	10-12	52°	84	N/A	18,000

T 12 L - HOOKLIFT HOIST (long)

FEATURES:

- 12,000 lb. capacity
- 11' - 14' container length range
- 48 degree dump angle
- Chassis requirements: 2 axle, 18,000 lb. recommended GVWR with 108" CA.



Model	Capacity in LBS	Container Length (ft.)	Dump Angle	Recommended Dimension (Inches)		Recommended GVW Rating (lbs)
				CA (4X2)	CT (6X4)	
T 12 L	12,000	11-14	48°	108	N/A	18,000